

<b>Model-No.:</b>		<b>Model:</b>
156 4420-FF-P		SEIZ® FIRE-FIGHTER PREMIUM

## Design & Construction

<b>Description:</b>	Fire fighter glove with supreme heat and cold protection. Anatomically shaped for perfect fit and wearers comfort. Excellent touch sensitivity with highest cut and abrasion resistance of palm. Equipped with the newly developed <b>SEIZ® Heat Absorber</b> on backhand. The woven material of the backhand incorporates all over reflective dots to provide additional safety.	
<b>Sizes:</b>	6/XXS, 7/XS, 8/S, 9/M, 10/L, 11/XL, 12/XXL	
<b>Color:</b> <b>Length:</b>	dark blue approx. 38 cm	

## Materials

<b>Palm:</b>	Double-Face knit of KEVLAR® with <b>SEIZ® Silicon Carbon Coating</b> .	
<b>Backhand:</b>	NOMEX® with <b>SEIZ® Heat Absorber</b> positioned to protect knuckles. Reflective dots all over the backhand. Elastic shirring at wrist.	
<b>Cuff:</b>	Wide cuff of NOMEX®. 3M Scotchlite™ reflective tape at cuff end, with double closure system. Hook and ring carabiner.	
<b>Lining:</b>	<b>SEIZ® Senso Touch</b> lining system. A technology to guarantee a strong and permanent link between KEVLAR® lining, GORE-TEX® membrane and the outer shell. Weight of the palm lining: 200 g/m² and backhand lining: 230 g/m².	
<b>Membrane:</b>	GORE-TEX® X-TRAFIT™ technologie.	

## User Information

<b>Care instructions:</b>		<b>Attention! Do not bleach or use oxidants.</b>
<b>Recommendations:</b>	The GORE-TEX® membrane is tightly fixed with the lining and the outer shell. We recommend, when pulling off the gloves, please hold on the fingertips with the other hand to avoid damaging the connection between membrane and outer shell.	
<b>Restrictions:</b>	These gloves do not offer protection against bacterial or chemical and electrical hazards. Gloves with attached GORE-TEX® membrane remain impervious to water only as long as the membrane is undamaged.	

## Pictograms and Performance level according to DIN EN 659:2008 (EN 659:2003 + A1:2008)

	<b>Parameter</b>	<b>Requirement</b>	<b>Results</b>
	Abrasion resistance (EN 388)	3 (2000 Cycles)	4
	Cut resistance (EN 388)	2 (Factor 2,5)	4
	Tear resistance (EN 388)	3 (50N)	4
	Puncture resistance (EN 388)	3 (100N)	3
	Burning behaviour (EN 407)	4	4
	Convective heat (EN 367/407)	4 (HTI24 ≥ 13s)	passed
	Radiant heat (EN ISO 6942)	RHTI24 ≥ 18s	passed
	Contact heat (EN 702)	t = 10s	passed
	Shrinkage (ISO 17493)	≤ 5% at 180°	passed
	Dexterity (EN 420)	1	4
	Removal of gloves (EN ISO 15383)	dry / wet ≤ 3s	passed
	Penetration of water (EN 344-1)	[...]	passed
	Penetration of liquids (ISO 15383)	[...]	passed
Penetration of liquid chemicals (EN 368)	[...]	passed	

<b>Testing Institute:</b>	0197 - TÜV Rheinland LGA Products GmbH – Tillystraße 2 – D-90431 Nürnberg/Germany
---------------------------	---

<b>Manufactured by:</b>	Friedrich Seiz GmbH – Neuhauser Str. 63 – D-72555 Metzingen/Germany
-------------------------	---

<b>For:</b>	KIVANC KIMYA SAN.VE TIC.A.S. Ikitelli OSB, Aykosan Sanayi Sitesi 2. Kisim 5. Ada C Blok / Ikitelli 34490 Istanbul / TURKEY Tel.: +90 (0212) 671 28 00   Fax: +90 (0212) 671 99 27   www.kivancgroup.com E-mail: info@kivancgroup.com
-------------	---