

Model-No.:		Model:
700302		SEIZ® TF-RED

Design & Construction

Description:	Fire fighter glove with supreme heat and cold protection. Anatomically shaped for perfect fit and wearers comfort. The heat resistant and special impregnated leather doesn't shrink even at high temperatures. Excellent touch sensitivity with high cut and abrasion resistance of palm. New SEIZ® Heat Absorber on the backhand as perfect heat and impact protection.	
Sizes:	6/XXS, 7/XS, 8/S, 9/M, 10/L, 11/XL, 12/XXL	
Colour: Length:	red / black approx. 36 cm	

Materials

Palm:	Black heat resistant impregnated special leather.	
Backhand:	Red NOMEX® with an especially developed SEIZ® Heat Absorber positioned to protect knuckles. Elastic shirring at wrist.	
Cuff:	Wide red NOMEX® cuff. Double closure system for perfect fit in extreme situations. Hook and ring carabiner.	
Lining:	SEIZ® Senso Touch lining system. The KEVLAR® lining is firmly fixed with the GORE-TEX® membrane.	
Membrane:	GORE-TEX® Non-Woven Membrane	

User Information

Care instructions:		Attention! Do not bleach or use oxidants.
Recommendations:	The GORE-TEX® Membrane at fingertips is tightly sewn on to the outer shell. We recommend, when pulling off the gloves, please hold on to the fingertips to avoid damaging the bond between membrane and outer glove.	
Restrictions:	This glove does not offer protection against bacterial or chemical and electrical hazards. Gloves with attached GORE-TEX® membrane remain impervious to liquids only as long as the membrane is undamaged.	

Pictograms and Performance level according to DIN EN 659:2008 (EN 659:2003 + A1:2008 + AC:2009)

 	Parameter	Requirement	Results
	Abrasion resistance (EN 388)	3 (2000 Cycles)	3
	Cut resistance (EN 388)	2 (Factor 2,5)	2
	Tear resistance (EN 388)	3 (50N)	4
	Puncture resistance (EN 388)	3 (100N)	4
	Burning behaviour (EN 407)	4	4
	Convective heat (EN 367/407)	4 (HTI24 ≥ 13s)	passed
	Radiant heat (EN ISO 6942)	RHTI24 ≥ 18s	passed
	Contact heat (EN 702)	t = 10s	passed
	Shrinkage (ISO 17493)	≤ 5% at 180°	passed
	Dexterity (EN 420)	1	4
	Removal of gloves (EN ISO 15383)	dry / wet ≤ 3s	passed
	Penetration of water (EN 344-1)	[...]	passed
Penetration of liquids (ISO 15383)	[...]	passed	
Penetration of liquid chemicals (EN 368)	[...]	passed	

Testing Institute:	Notified party: 0197 - TÜV Rheinland LGA Products GmbH – Tillystraße 2 – D-90431 Nürnberg/Germany
---------------------------	--

Manufactured by:	Friedrich Seiz GmbH – Neuhauser Str. 63 – D-72555 Metzingen/Germany
-------------------------	---

For:	KIVANC KIMYA SAN.VE TIC.A.S. Ikitelli OSB, Aykosan Sanayi Sitesi 2. Kisim 5. Ada C Blok / Ikitelli 34490 Istanbul / TURKEY Tel.: +90 (0212) 671 28 00 Fax: +90 (0212) 671 99 27 www.kivancgroup.com E-mail: info@kivancgroup.com
-------------	---